



## Product Profile

- Fiber optic connectivity without cumbersome and costly external converters
- 10/100 Ethernet for the highest data rates possible
- VoIP optimization to leverage the wireless LAN for voice and data
- Integrated Power over Ethernet solution eliminates expensive cabling
- IEEE 802.11b compliant and Wi-Fi certified ensures interoperability
- 11 Mbps performance supports bandwidth-intensive applications
- NEMA4/IP54 case withstands harsh environments

### MobileLAN™ access 2100

MobileLAN™ access 2100 is an 11 Mbps wireless access point available for high-speed, high-throughput, demanding environments. Compliant with 802.11b standards, MobileLAN access 2100 sets a new standard in access points with advanced features and better performance. Housed in a NEMA4/IP54 case with heater options, MobileLAN access 2100 is the ideal access point for harsh environments where cold temperatures, small airborne particles and moisture are prevalent.

#### High performance wireless communications

Fiber optic network connectivity is now possible on MobileLAN access 2100 via an MT-RJ connector.

Wireless service on 100 Mbps networks is now achievable with 10Base-T/100Base-Tx compatibility on MobileLAN access 2100. It auto negotiates with the device it is connected to allowing the data rate to be set at the highest rate at which both devices can communicate.

Intermec's patented dual radio support as well as support for S-UHF, 900Mhz and Open Air technologies continue to be available on MobileLAN access 2100.

Recognizing that Ethernet can have data rates as high as 100Mbps and that radio data rates are no more than 11 Mbps, Intermec designed a more efficient method for its access points to forward packets from the Ethernet to the radios. MobileLAN access 2100 uses hardware-based packet filtering, which ensures fewer dropped packets, less network congestion and better overall performance.

MobileLAN access 2100 leads the industry with seamless IP tunneling. This feature eliminates the requirement to have the routing application reside in the client. The technology supports wall-to-wall bridging, which allows your wireless network to grow without the expense of expanding the wired backbone.

MobileLAN access 2100 expands the options available to IT managers with integrated Power over Ethernet and support for VoIP.

IP addresses are easier and less expensive to administer on MobileLAN access 2100 with DHCP (Dynamic Host Configuration Protocol) server functionality. MobileLAN access 2100 can use any standard RADIUS server for optimum network security. Additional security is provided through WEP key management.

**Physical Characteristics**

**Length:** 355 mm (14.0")  
**Height:** 95 mm (3.75")  
**Width:** 236 mm (9.3")  
**Weight:** 2.63 kg (5.8 lb)  
**Input Voltage:** 100-240 VAC Auto Ranging Power Supply  
**Input Power:** 15 Watts Optional Heater Additional 75 Watts  
 Supports dual radio and mixed dual radio operation wireless bridging DHCP client and server NAT server radius server

**Wireless LAN Characteristics**

**802.11b Wireless Radio**  
**Frequency Band:** 2.4 GHz, actual frequencies vary by country.  
**Radio Type:** IEEE 802.11b (11 Mbps)  
**Modulation:** Direct Sequence Spread Spectrum (CCK, DQPSK, DBPSK)  
**Radio Power Output:** 15 dBm  
**Radio Data Rate:** 11 Mbps High/5.5 Mbps Medium/2 Mbps Standard/1 Mbps low Automatic fallback for increased range  
**Channels:** United States (FCC) 11 Channels, Europe (ETSI) 13 Channels, other countries per local regulations.  
**Bit Error Rate:** Better than 10<sup>-5</sup>

Range	1Mbps	2 Mbps
Open Environment	1750ft (533m)	1300ft (396m)
Semi-Open	375ft (114m)	300ft (91m)
Closed Environment	165ft (50m)	130ft (40m)
Unlimited range with roaming		
Receiver Sensitivity:	-95 dBm	-92 dBm

Range	5.5 Mbps	11 Mbps
Open Environment	885ft (270m)	525ft (160m)
Semi-Open	230ft (70m)	165ft (50m)
Closed Environment	115ft (35m)	80ft (24m)
Unlimited range with roaming		
Receiver Sensitivity:	-87 dBm	-82 dBm

**Security:** IEEE 802.11 Wired Equivalent Privacy (WEP) standard, WEP64 and WEP128 are supported

**2.4 GHz OpenAir Wireless Radio**

**Frequency Band:** 2.4 GHz, actual frequencies vary by country.  
**Radio Type:** WLI Forum OpenAir  
**Radio Power Output:** 500 mW /100 mW (Europe)  
**Radio Data Rate:** 1.6 Mbps per channel. 800 Kbps fallback rate for extended range.

**North America**  
 Corporate Headquarters  
 6001 36<sup>th</sup> Avenue West  
 Everett, Washington 98203  
 tel: 425.348.2600  
 fax: 425.355.9551

**Systems & Solutions**  
 550 2nd Street S.E.  
 Cedar Rapids, Iowa 52401  
 tel: 319.369.3100  
 fax: 319.369.3453

**Media Supplies**  
 9290 Le Saint Drive  
 Fairfield, Ohio 45014  
 tel: 513.874.5882  
 fax: 513.874.8487

**Europe/ Middle East & Africa**  
 Headquarters  
 Sovereign House  
 Vastern Road  
 Reading RG1 8BT  
 United Kingdom  
 tel: 44.118.987.9400  
 fax: 44.118.987.9401

**Asia**  
**Asia Regional Office**  
 25-16 International Plaza  
 10 Anson Road  
 Singapore 079903  
 tel: 65.6324.8391  
 fax: 65.6324.8393

**Australia**  
 Level 7, 200 Pacific Highway  
 Crows Nest, NSW 2065  
 Australia  
 tel: 61.2.9492.4400  
 fax: 61.2.9954.6300

**South America & Mexico**  
 Latin America Headquarters  
 17921 B Skypark Circle  
 Irvine, California 92614  
 tel: 949.442.9393  
 fax: 949.757.1687

Intermec South America Ltda.  
 Rua Arandu 1544-15 andar  
 Edificio Itavera  
 Brooklin Novo 04562-031  
 Sao Paulo, SP  
 Brazil  
 tel: 55.11.5501.2070

**Mexico**  
 Tamulipas 141, Primero Piso  
 06140 Mexico, D.F.  
 tel: 525.55.211.1919  
 fax: 525.55.211.8121

**Software Upgrades:** Downloadable using Web Browser or TFI over the network or serial port.

**Management**

**Management Interfaces:** SNMP; Web browser-based manager; serial port, or Telnet via RF, serial and Ethernet.  
**SNMP Version 1 Agent supporting:**  
**SNMP Traps:** Cold start, authorization violation, MobileLAN access point enterprise specification  
**SNMP MIBs:** RFC 1213, RFC 1398, RFC 1493, MobileLAN access point MIB

**Environment**

**Operating:**  
**Standard Unit:** -25° to 70°C (-13° to 158°F)  
**Heater Option:** -30° to 70°C (-22° to 158°F)  
**Heater Option with insulated bag:** -30° to 0°C (-22° to 32°F)  
**Storage Temperature Range:** -40° to 70°C (-40° to 158°F)  
**Humidity (Non-Condensing):** 10 to 90% relative humidity, non-condensing  
**Industrial Sealing:** IP54 (NEMA 4)

**Accessories**

- Mounting Brackets
- Wide selection of RF Antennas and Cables

**Regulatory Approvals**

FCC Part 15.247 Certified; Canada RSS 210 Certified; ETS 300 328 Type Approved; EN 55022 / CISPR 22 Class A; FCC Part 15 & ICES-003 Class A; SCT Certification, NOM-EM-121; AS 3548, C tick Marked; Compliant with all European Directives, CE Marked (ETS 300 826); UL Listed, UL 1950/C22.2 #950 IEC; 60529-IP53 and C22.2 #94-ENC3.5; Non-incendive 2.4 GHz and 900 MHz antenna circuits UL Listed, UL 1604 & C22.2 #213 for Div 2; Class I-Groups A, B, C & D; Class II-Groups F & G; Class III; TÜV Licensed, EN 60950 & EN 60529-IP53; NYCE Certified, NOM 19

Intermec reserves the right to make changes without notice to any products herein for any reason at any time, including but not limited to improving the reliability, form, fit, function or design. Please contact Intermec for a current price list and availability.

**Worldwide Fax Document Retrieval Service**  
 800.755.5505  
 (North America Only)  
 tel: 650.556.8447

**Internet**  
 www.intermec.com

**Sales**  
 800.347.2636  
 (toll free in N.A.)  
 tel: 425.348.2726

**Service and Support**  
 800.755.5505  
 (toll free in N.A.)  
 tel: 425.356.1799

Copyright © 2003 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A.  
 608464-01D 2/03

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.

